

# WL 37 Wheel Loader 3,7 t

Item Number: 0610145

# WL 37

## Strong pulling powers

>> Cost, benefit, quality: The Wacker Neuson wheel loaders WL 36 and WL 37 pass any test with flying colors. Even the toughest tests. Independent of which model you choose. Both guarantee safe and controlled operation. They feature precise handling, enormous engine power and a respectable shovel volume. Furthermore, the WL36 and the WL37 are very economical in their consumption and have low emissions. Their emission values are convincing just like anything else about and in them. <<



## Additional Advantages

- State-of-the-art diesel engines by Perkins and Deutz - powerful performance and economical in their consumption. Their robust design ensures a long life. Even with heavy use.
- The light, spacious ROPS and FOPS tested cab offers protection and freedom of movement for the operator. The 360° visibility enables safe and controlled operation on any construction site. Cab and seat are well sprung.
- The cab can be tilted to the side easily and comfortably. All major components can be accessed quickly and maintenance and repairs are easy to carry out.
- High stability against overturning due to the low machine center of gravity and good load distribution.
- The compact wheel loaders develop enormous biting forces due to the special PZ kinematics. Tons of material can be moved effortless - placed exactly on target.
- Fast changes: Thanks to the hydraulic quick change system, the add-on equipment is easily exchanged.

Description	Metric	Imperial
Motor type	Deutz (BF4M 2011)	
Power	56,0 kW	- PS
Speed	2.300 1/min	- rpm
Speed	0 - 20 km/h	- mph
Operating weight	3.730 kg	- lb
Shovel capacity	0,6 m <sup>3</sup>	- ft <sup>3</sup>
Overall length with standard shovel	4.960 mm	- in
Total width, standard	1.560 mm	- in
Height of cab	2.310 mm	- in
Total working height	4.056 mm	- in
Max. height of bucket pivot point	3.239 mm	- in
Inside turning radius	1.303 mm	- in
Max. lifting force	3.706 kg	- lb
Tipping load with bucket	2.688 kg	- lb
Tipping loads with bucket (articulated)	2.228 kg	- lb
Tipping loads with pallet fork (straight)	2.203 kg	- lb
Tipping loads with pallet fork (articulated)	1.853 kg	- lb
Breakout force	3.907 daN	- lb
Height over bar	- mm	- in

### Standard Package - WL 37

includes operator's manual and parts book

**Please refer to our Price List and Ordering Guide for complete accessory information.**

Specifications may change due to continuous product development. Users are advised to consult Wacker Neuson's Operator's Manual and website for specific information regarding the engine power rating. Actual power output may vary due to conditions of specific use.

Generated on Thursday, April 14, 2011

